

## SECTION 1: Identification of the substance/Preparation and of the company/Undertaking

#### 1.1. Product identifier

Product name LUXURY % 70 ISOPROPYL ALCOHOL WITH WINTERGREEN

#### 1.2. Details of the manufacturer of the safety data sheet

sedayuca@tsmbrands.com.tr

300-2 Route 17 South, Unit D, Lodi, NJ 07644

Web: www.tsmbrands.com

#### 1.3. Emergency telephone number

1-800-424-9300

## 1.4. National poison Information centre

1-800-222-1222

#### **SECTION 2: Hazards Identification**

#### 2.1. Classification of the substance or mixture

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity (single exposure) Category 3
Target Organs - Central nervous system (CNS).

#### 2.2. Label elements

#### **Hazard Statements**

Highly flammable liquid and vapor

Causes serious eye irritation

May couses drowsiness or dizziness



#### Signal Word

Danger

# **Precautionary statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed

Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

In case of fire: Use CO2, dry chemical, or foam for extinction

Store in a well-ventilated place. Keep container tightly closed Store locked up

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC) None identified

H336 May cause respiratory irritation.

P210 Keep away from heat, hot surfaces, open flames, sparks. – No smoking

P102 Keep out of the reach of children.
P233 Keep container tightly closed
P234 Store only in the original container.

P261 Avoid breathing mist

P303 + P361 + P353 If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower

P305+P351+P338 In case of contact with eyes: Rinse cautiously with water for several minutes. Plugged in and easy

to do remove contact lenses, if. Continue rinsing.

P304+P340 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER or doctor /physician if you feel unwell

P410+P403 Protect from sunlight. Store in a well ventilated area.

P370+P378 In case of fire: Use dry chemical powder, alcohol –resistant foam, carbon dioxide (CO2) to

extinguish.

#### SECTION 3: Composition/information on ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	64.7
Water	7732-18-5	35.3
Wintergreen oil	68917-75-9	0,1

#### **SECTION 4:First aid measures**

General advice

If symptoms persist, call a physician.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Get medical attention.

Skin Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical

attention if symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache,

dizziness, tiredness, nausea and vomiting

# **SECTION 5: Fire fighting measures**

## 5.1. Suitable extinguishing media

CO 2, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 12°C

Method - No information available

Autoignition Temperature 399 °C / 750.2 °F

**Explosion Limits** 

Upper 12.7 vol %

Lower 2.0 vol %

Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

# 5.2. Special hazards arising from the chemical

Flammable properties Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and

 $flash\ back.\ Containers\ may\ explode\ when\ heated.\ Vapors\ may\ form\ explosive\ mixtures\ with\ air.$ 

# 5.3. Hazardous combustion products

Carbon monoxide (CO). Carbon dioxide (CO2).peroxides.

## 5.4. Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: Accidental release measures**

#### 6.1. Personel precautions, protective equipment and emergeny procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all

Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for containment and clean

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### 7.2. Specific end use(s)

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

## **SECTION 8: Exposure control/Personal protection**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m³ TWA: 400 ppm TWA: 980 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³	TWA: 200 ppm STEL: 400 ppm

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are

close to the workstation location.

Wear appropriate protective eyeglasses or chemical safety goggles as described Eye/face Protection

by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European

Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European

Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved

respirator if exposure limits are exceeded or if irritation or other symptoms

areexperienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical

Physical State	Liquid
Appearance	Liquid
Color	Colourless
Odor	Alcohol odour Stuffy odour Mild odour
Odor Threshold	No information available
рН	Not applicable
Melting Point/Range	-89 °C
Boiling Point/Range	82 °C / 179.6 °F
Flash Point	12 °C
Evaporation Rate	2.3 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	12.7 vol %
Lower	2.0 vol %
Vapor Pressure	44 hPa (20°C)
Vapor Density	2.1 (Air = 1.0)
Specific Gravity	0,88g/ml
Solubility	Miscible with water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	399 °C / 750.2 °F
Decomposition Temperature	No information available
Viscosity	No informationavailable
l	

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

None known, based on information available

#### 10.2. Condition to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

#### 10.3. Incompatible materials

Strong oxidizing agents, Strong acids, Metals Hazardous

#### 10.4. Incompatible materials

Carbon monoxide (CO), Carbon dioxide (CO2), peroxides Hazardous

#### **SECTION 11: Toxicological information**

**Acute Toxicity** 

**Product Information** 

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component LD50 Oral LD50 Dermal LC50 Inhalation

Isopropyl alcohol 5840 mg/kg (Rat) 13900 mg/kg (Rat) 12870 mg/kg (Rabbit) 72.6 mg/L (Rat) 4 h

Water - - -

Toxicologically Synergistic

Products

: No information available

 $Delayed and immediate \,effects \,as \,well \,as \,chronic \,effects \,from \,short \,and \,long-term \,exposure$ 

Irritation Severe eye irritant

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component CAS-No IARC NTP ACGIH OSHA Mexico
Isopropyl alcohol 67-63-0 Not listed Not listed Not listed Not listed Not listed Water 7732-18-5 Not listed No

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT -single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated

### **SECTION 12: Ecological information**

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h	LC50: = 9640 mg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	flow-through (Pimephales	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	promelas)	phosphoreum 5 min	
	EC50: > 1000 mg/L, 96h	LC50: > 1400000 μg/L, 96h		
	(Desmodesmus	(Lepomis macrochirus)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
		static (Pimephales promelas)		

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Isopropyl alcohol	0.05

## **SECTION 13: Disposal consideration**

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

## **SECTION 14: Transport information**

DOT

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3

Packing Group II

TDG

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3

Packing Group II

IATA

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3

Packing Group II

IMDG/IMO

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3

Packing Group II

# **SECTION 15: Regulatory information**

# **United States of America Inventory**

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory F I a g s
Isopropyl alcohol	67-63-0	X	ACTIVE	-
WATER	7732-18-5	X	ACTIVE	-

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	64.7	1.0

U.S. Federal Regulations

## **SECTION 16: Other information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.